FORD TRUCKS 3333 EURO3



Basic Features				
Vehicle Type	Road Truck			
Axle	6x4			
Emission	Euro 3			
Cabin Type	Day Cab			
Wheelbase (mm)	4500			
Engine				
Туре	Ecotorq 9 Litres			
Displacement (cc)	8974			
Diameter x Stroke	115 mm x 144 mm			
Power	330 PS (243 kW) @ 1900 rpm			
Torque	1300 Nm @ 1200 - 1700 rpm			
Compression Ratio	17,6 : 1			
Oil Filling Volume	30 L			
Coolant Volume	46L			
Transmission				
Clutch	430 mm Single Disc			
Manuel Transmission / Ratios (1. gear - 9. gear)	9 + 1 Speed (9,40 - 0,75)			
Steering				
	Power Assisted Single Circuit			
Chassis				
Chassis Thickness	10 mm with Reinforcement			
Chassis Strength	500 MPa			
Suspension (Front / Rear)	Parabolic Leaf Springs / Parabolic Tandem Suspension			
Axle	Hub Reduction			
Axle Ratio	4,87			
Tyres	315/80 R 22,5			
Wheel Rim	22,5 x 9 Steel			
Braking System				
Brakes (Ø mm x mm Length)	430 x 45 - Disc Brake Z-Cam Brake System			
Braking System	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater			
Engine Brake Power	max. 180 kW (Engine Level)			
Electrical System				
Battery	24 V, 2 x 12 V 180 Ah			
Alternator / Starter Motor	130 A / 6,5 kW			
Tanks				
Fuel Tank	410 L Aluminium			



Sharing the load

Dimensions (mm)				
Front Overhang			1500	
Wheelbase			4500	
Overall Length			9217	
Distance Between 2 nd and 3 th Wheel Centers			1350	
Overall Cab Length			1820	
Overall Vehicle Height			3210	
Overall Vehicle Width (Excluding Mirrors)			2540	
Chassis Width			770	
Rear Overhang			1750	
Useful Chassis Length			6690	
Chassis Height - Front			1114	
Chassis Height - Rear			1146	
Ground Clearance - Front			373	
Ground Clearance - Rear			258	
Weights (kg)	1. Axle	2. Axle	3. Axle	Total
Technically Permissible Weights	8000	13400	13400	26000
Kerb Weight	4829	2230	2259	9318
Payload	2120	7528	7304	16682

STANDARD EQUIPMENT

- Radio/CD Player
- Air Conditioner
- Cruise Control
- Disk Brake
- Engine Brake
- Electrically Operated Windows
- Electrically Operated and Heated Side Mirrors
- Electrically Operated Headlamp Leveling
- Rake and Reach Adjustable Steering Column
- Heated and Air Suspended Driver Seat
- Lumbar Support
- Front and Rear Vehicle Antiroll Bar
- Anti-Lock Brake System (ABS)
- Brake Lining Wear Indicator
- Immobilizer
- Single Key with Remote Control and Central Locking
- Home Safe Light
- Approach Light
- Differential Lock
- Switchable Air Compressor for Improved Fuel Economy
- Rear Window
- Short Bumper
- Tyre Pressure Gauge
- Horizontal Exhaust
- Tachometer Simulator Unit (TSU)

OPTIONAL EQUIPMENT

- Wet Type Cab Heater
- Power Cab Tilting
- Engine Driven PTO & Interior Control Unit
- Automatic Traction Control
- Lateral Protection
- Mechanical Tachograph
- Full Trailer Option (O2 O3)
- Vertical Exhaust
- ADR
- Less Front Spare Wheel Option
- Manually Operated Sunroof

This leaflet includes products designed for Ford Trucks vehicles. It provides information about the current technical specifications and the standard or optional accessories available as of the date it was issued. Features of standard and optional accessories of the vehicles may be changed from time to time. For this reason, please consult our Authorized Dealers to obtain updated and accurate information on the features of the vehicle you wish to buy. For the aforementioned reason, this leaflet does not constitute an assurance as to the specifications listed herein. The images used in this leaflet may be different from the vehicles on sale. The technical specifications provided herein are for standard vehicles. Selection of any optional accessories might cause differences from these specifications.